

ACCESSPLUS® II DOUBLE-HINGED WALL-MOUNT CABINET

PROTECTING YOUR ADVANTAGE

Hoffman®

A PENTAIR COMPANY

Broad selection of models support heavy-duty load capacities, deliver time-saving features.

ACCESSPLUS® II expands Hoffman's comprehensive family of networking solutions. The versatile wall-mount cabinet handles network equipment weighing 250 to 500 lbs. and is available in a wide variety of cabinet sizes. The rugged cabinets feature quick-release latching for easy access to the backside of mounted equipment, and latch-free sides allow cabinet installation in tight spaces and corners. Available in solid-door models, ACCESSPLUS II also offers tinted safety glass door options, which deliver greater clarity, strength and scratch resistance than plexiglass.

Two cable-entry options and extra-wide models provide flexible cable management to meet versatile application requirements.

Along with standard cable entry knockouts, ACCESSPLUS II is available with a gland plate designed to accommodate pre-wired patch panel installation, making it an ideal solution for retrofit applications. For extra cable capacity and efficient cable routing, the 28-inch wide model delivers vertical cable management with Hoffman's patent-pending CABLETEK™ fingers.

ADVANTAGES AND FEATURES

- **Best-in-class aesthetics** - large window, rounded edges and hidden welds provide an appealing appearance
- **Increased load capacity**
 - patent-pending hinge supports loads from 250 to 500 lbs., depending on cabinet size
- **Ease of assembly** - tool-less hinges allow quick separation of back and center section for easy one-person installation
- **Better equipment access**
 - quick-release latching makes opening and closing the center section easy
- **More cable capacity** - 28-inch wide models include vertical cable managers
- **Retrofit gland-plate cable entry**
 - secure pre-terminated patch panels and equipment



28-inch wide model with vertical cable management



Gland-plate option provides an ideal solution for many retrofit applications



ACCESSPLUS® II Double-Hinged Wall-Mount Cabinets

30-inch deep models
now available



WINDOW DOOR

Part Number	H x W x D (in.)
EWMW242418	24 x 24 x 18
EWMW362418	36 x 24 x 18
EWMW482418	48 x 24 x 18
EWMW602418	60 x 24 x 18
EWMW722418	72 x 24 x 18
EWMW242425	24 x 24 x 25
EWMW362425	36 x 24 x 25
EWMW482425	48 x 24 x 25
EWMW602425	60 x 24 x 25
EWMW722425	72 x 24 x 25
EWMW242430	24 x 24 x 30
EWMW362430	36 x 24 x 30
EWMW482430	48 x 24 x 30

NUMEROUS OPTIONS. INNOVATIVE SOLUTIONS.

SOLID DOOR

Part Number	H x W x D (in.)
EWMS242418	24 x 24 x 18
EWMS362418	36 x 24 x 18
EWMS482418	48 x 24 x 18
EWMS242425	24 x 24 x 25
EWMS362425	36 x 24 x 25
EWMS482425	48 x 24 x 25



WINDOW DOOR WITH CABLE MANAGER

Part Number	H x W x D (in.)
EWMW242825	24 x 28 x 25
EWMW362825	36 x 28 x 25
EWMW482825	48 x 28 x 25

WINDOW DOOR WITH GLAND PLATE

Part Number	H x W x D (in.)
EWMWG242418	24 x 24 x 18
EWMWG362418	36 x 24 x 18
EWMWG482418	48 x 24 x 18
EWMWG242425	24 x 24 x 25
EWMWG362425	36 x 24 x 25
EWMWG482425	48 x 24 x 25



TURN TO HOFFMAN FOR YOUR NETWORKING SOLUTIONS

For over 60 years, Hoffman has defined excellence in enclosures. With thousands of offerings in every size and shape, we're the experts in providing solutions for a broad range of networking applications. To learn more, contact your local Hoffman sales office or visit hoffmanonline.com



FAN KITS

Part Number	Used For
EWMF1	18" deep cabinets
EWMF2	25" and 30" deep cabinets

INDUSTRY STANDARDS

UL 508A; Type 1;
File No. E61997
cUL Listed per CSA C22.2
No. 182.4; File No. E230874

EIA 310-D
NEMA/EEMAC Type 1
EIC 60529 IP20
Per BICSI TDDMM Tenth edition,
Chapter 7, Telecommunication
Enclosures (TE)

FRONT DOOR

- Composite frame (injection molded top and bottom with extruded composite sides)
- Door opens 140°
- Field-reversible (left or right) hinge
- Quarter-turn key lock, two keys included
- Window door is scratch-resistant ¼-inch tinted safety glass
- Solid door has 16 gauge steel insert with matching black finish

CENTER SECTION

- Welded 14 gauge steel
- Solid top of center section provides protection against falling debris
- Ventilated sides (fans can be added)
- Self-latching closure connects center section to wall section
- Self-alignment ramp supports center section to wall section
- Heavy duty center-to-rear section hinge with quick-release self-retained hinge pin simplifies wall installation

RACK-MOUNTING ANGLES

- 12 gauge, plated steel
- EIA universal spaced 19-inch rack-mounting holes
- RU marked from bottom to top
- Tapped 10-32 holes, 20 mounting screws included

REAR WALL SECTION

- Welded 14 gauge steel
- Radius corners; no sharp edges
- Available with knockouts or gland plates
- Raised pads for accessory mounting
- Cable tie-down points for cable management
- Keyhole mounting holes allow wall section to be mounted over fasteners and facilitates installation
- Three cable-entry grommets

FINISH

Phosphatized steel coated with RAL 9005 black light-textured, low-gloss polyester powder paint. Other finishes available—contact Hoffman Customer Service for more information.

PROTECTING YOUR ADVANTAGE



USA

2100 Hoffman Way
Anoka, Minnesota 55303-1745 U.S.A.
Tel: 763-422-2661
Fax: 763-422-2588
Customer Service: 763-422-2661

Canada

111 Grangeway Avenue, Suite 504
Scarborough, Ontario M1H 3E9
Tel: 416-289-2770
Fax: 416-289-2883
1-800-668-2500 (Canada only)

Mexico

Hoffman Enclosures Mexico, S. de R. L. de C. V.
Arquimedes No. 33
Piso 1
Col. Palmas Polanco
Mexico, DF
CP 11560
Tel: (55) 5280-1596
Fax: (55) 5280-8827 / 5280-8167

For worldwide locations, see
hoffmanonline.com